

# Portable Type Pressure Steam Sterilizer ,24L,30L



The new generation of portable disinfecting apparatus developed by our factory has the advantage of high performance safety and reliable. It is convenient and quickly to handle and the controlling system has completely function. The apparatus pertain to pressure vessel products and comply with national content regulations of the design and manufactures.

**Features:**

- 1 ,Water supply cut protecting equipment.
- 2 ,Digital display working status.
- 3 ,Self inflating type seal.
- 4 ,Fixation pressure device.
- 5 ,Automatic discharge of cold air.
- 6 ,Electric heating.
- 7 ,It is a pressure vessel products(comply with national content regulations the design and manufacture).

**TECHNICAL PARAMETERS**

<b>Parameter /Model</b>	<b>DSX-280KB24</b>	<b>DSX-280KB30</b>
<b>Configuration</b>	Automatic control	Automatic control
<b>Material/Thickness(mm)</b>	Stainless steel/2.0	Stainless steel/2.0
<b>Volume/ GW</b>	24L / 20Kg	30L / 24 Kg
<b>Voltage / Power</b>	220V / 2 Kw	220V / 2 Kw
<b>Packing size (L x W x H mm)</b>	405×405×665	405×405×715
<b>Sterilization chamber volume(diameter x height mm)</b>	280×390	280×470
<b>Liner (diameter x height mm)/ Quantity</b>	Basket x1 260×290	Basketx1 260×370
<b>Shift place type of quick-open cover structure</b>	YES	YES
<b>Intelligent auto-control sterilization cycle</b>	YES	YES
<b>Pressure self-locking device</b>	YES	YES
<b>Interactive safety interlock device</b>	YES	YES
<b>Water supply cut protecting equipment</b>	YES	YES
<b>Digital window display working status</b>	YES	YES
<b>Time setting range</b>	0-99 h	0-99 h 0-99 h
<b>Working Pressure</b>	0.142 Mpa	0.142 MPa
<b>The working temperature</b>	50~128 °C	50~128 °C
<b>Double scale numerical indication pressure gauge</b>	YES	YES
<b>Self infating type seal</b>	YES	YES
<b>Fixation pressure device</b>	YES	YES
<b>Automatic discharge of cold air</b>	YES	YES
<b>Electric heating</b>	YES	YES